

JIS 溶接鋼管

SUS304											
材質											
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
13.8	2	4000	0.588	TP	A	38	1.5	4000	1.36	TP	A
17.3	2	4000	0.762	"	"	42.7	1.5	4000	1.54	"	"
	2.5	4000	0.922	"	"		2	4000	2.03	"	"
	3	4000	1.07	"	"		6000		"	"	
21.7	1.5	4000	0.755	"	"	48.6	3	4000	2.97	"	"
	2	4000	0.981	"	"		6000		"	"	
		6000		"	"		3.5	4000	3.42	"	"
	2.5	4000	1.2	"	"		6000		3.42	TP	A
		6000		"	"		4	4000	3.86	"	"
	3	4000	1.4	"	"		6000		1.42	"	"
25.4	1.5	4000	0.893	"	"	50.8	2	4000	2.32	"	"
	2	4000	1.17	"	"		3	4000	3.41	"	"
27.2	1.5	4000	0.96	"	"	60.5	6000		"	"	
	2	4000	1.26	"	"		3.5	4000	3.93	"	"
		6000		"	"		4	4000	4.44	"	"
	2.5	4000	1.54	"	"		6000		"	"	
		6000		"	"		5.1	4000	5.53	"	"
	3	4000	1.81	"	"		6000		3.57	"	"
32	2	4000	1.49	"	"	76.3	2	4000	2.2	"	"
	3	4000	2.17	"	"		6000		"	"	
34	1.5	4000	1.21	"	"	76.3	3.5	4000	4.97	"	"
	2	4000	1.59	"	"		6000		"	"	
		6000		"	"		4	4000	5.63	"	"
	2.5	4000	1.96	"	"		6000		"	"	
	3	4000	2.32	"	"		5.5	4000	7.54	"	"
		6000		"	"		6000		3.7	"	"
	3.5	4000	2.66	"	"		3	4000	5.48	"	"
		6000		"	"		6000		"	"	
4	4000	2.99	"	"	3.5	4000	6.35	"	"		
						6000		"	"		

JIS 溶接鋼管

SUS304												
材質												
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	
76.3	5	4000	8.88	TP	A	165.2	7.1	4000	28	TP	A	
	5.2	4000	9.21	"	"			6000				"
	7	4000	12.1	"	"		190.7	3	4000	14	"	"
89.1	2	4000	4.34	"	"	216.3	3	4000	15.9	"	"	
	3	4000	6.43	"	"			4				4000
		6000		"	"		6.5	4000	34	"	"	
		4	4000	8.48	"	"	8.2	4000	42.5	"	"	
			6000	8.48	TP	A	12.7	4000	64.4	"	"	
		5.5	4000	11.5	"	"	267.4	3	4000	19.8	"	"
		5.5	6000		"	"		4	4000	26.2	"	"
	7.6	4000	15.4	"	"	267.4	6.5	4000	42.2	"	"	
101.6	3	4000	7.37	"	"		9.3	4000	59.8	"	"	
	4	4000	9.72	"	"		15.1	4000	94.9	"	"	
114.3	2	4000	5.59	"	"	318.5	3	4000	23.6	"	"	
	3	4000	8.32	"	"			4				4000
		6000		"	"		4.5	4000	35.2	"	"	
		4	4000	11	"	"		6000		"	"	
			6000		"	"	6.5	4000	50.5	"	"	
		6	4000	16.2	"	"	10.3	4000	79.1	"	"	
			6000		"	"	355.6	5	4000	43.7	TP	YSA
	8.6	4000	22.6	"	"	8		4000	69.3	"	"	
139.8	3	4000	10.2	"	"		11.1	4000	95.3	"	"	
	3.5	4000	11.9	"	"	406.4	5	4000	50	"	"	
	4	4000	13.5	"	"			8				4000
	5	4000	16.8	"	"		12.7	4000	125	"	"	
		6.6	4000	21.9	"	"				"	"	
152.4	3	4000	11.2	"	"					"	"	
165.2	3	4000	12.1	"	"					"	"	
	3.5	4000	14.1	"	"					"	"	
	4	4000	16.1	"	"					"	"	
	5	4000	20	"	"					"	"	
	6	4000	23.8	"	"					"	"	

JIS 溶接鋼管

SUS316											
材質											
外徑 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外徑 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
21.7	2	4000	0.988	TP	A	216.3	4	4000	21.3	TP	A
	2.5	4000	1.55	"	"		6.5	4000	34.2	"	"
	3	4000	1.82	"	"		8.2	4000	42.8	"	"
27.2	2	4000	1.26	"	"	267.4	4	4000	26.4	"	"
	2.5	4000	1.55	"	"		6.5	4000	42.5	"	"
	3	4000	1.82	"	"		9.3	4000	60.2	"	"
34	3	4000	2.33	"	"	318.5	4.5	4000	35.4	"	"
	3.5	4000	2.68	"	"		6.5	4000	50.8	"	"
42.7	3	4000	2.99	"	"		10.3	4000	79.6	"	"
	3.5	4000	3.44	"	"						
	4	4000	3.88	"	"						
48.6	3	4000	3.43	"	"						
	4	4000	4.47	"	"						
60.5	3	4000	4.32	"	"						
	3.5	4000	5	"	"						
	4	4000	5.67	"	"						
76.3	3	4000	5.51	"	"						
	3.5	4000	6.39	"	"						
	5.2	4000	9.27	"	"						
89.1	3	4000	6.48	"	"						
	4	4000	8.53	"	"						
	5.5	4000	11.5	"	"						
114.3	3	4000	8.37	"	"						
	4	4000	11.1	"	"						
	6	4000	16.3	"	"						
139.8	3	4000	10.3	"	"						
	3.5	4000	12	"	"						
	5	4000	16.9	"	"						
	6.6	4000	22	"	"						
165.2	3.5	4000	14.2	"	"						
	5	4000	20.1	"	"						
	7.1	4000	28.1	"	"						

JIS 溶接鋼管

SUS316L													
材質													
外徑 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外徑 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上		
13.8	2	5500	0.592	TP	A	114.3	4	4000	11.1	TP	A		
		6000		"	"			6	4000	16.3	"	"	
21.7	2	4000	0.988	"	"	139.8	3.5	4000	12	"	"		
		2.5	4000	1.2	"			"	5	4000	16.9	"	"
		3	4000	1.41	"			"					
27.2	2	4000	1.26	"	"	165.2	3.5	4000	14.2	"	"		
		2.5	4000	1.55	"			"	5	4000	20.1	"	"
		3	4000	1.82	"			"					
34	2	4000	1.6	"	"	216.3	3	4000	16	"	"		
		3	4000	2.33	"			"	4	4000	21.3	"	"
		3.5	4000	2.68	"			"					
42.7	2	4000	2.04	"	"	267.4	4	4000	26.4	"	"		
		3	4000	2.99	"			"	6.5	4000	42.5	"	"
		3.5	4000	3.44	"			"					
		4	4000	3.88	"			"					
48.6	3	4000	3.43	"	"	318.5	4.5	4000	35.4	"	"		
		4	4000	4.47	"			"	6.5	4000	50.8	"	"
		5.1	4000	5.56	"			"					
60.5	2	4000	2.93	"	"								
		3	4000	4.32	"							"	
		3.5	4000	5	"							"	
		4	4000	5.67	"							"	
76.3	2	4000	3.73	"	"								
		3	4000	5.51	"							"	
		3.5	4000	6.39	"							"	
		5.2	4000	9.27	"							"	
89.1	2	4000	4.37	"	"								
		3	4000	6.48	"							"	
		4	4000	8.53	"							"	
		5.5	4000	11.5	"							"	
114.3	2	4000	5.63	"	"								
		3	4000	8.37	"							"	