

ASTM シームレス鋼管

材質

ASTM A312 TP316/316L-S

* 在庫終了次第A312M/SA312Mに変更されます。

外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	
13.72	2.24	6000	0.645			73.03	3.05	6000	5.35			
	3.02	6000	0.81				5.16	6000	8.78			
21.34	2.11	6000	1.02			88.9	7.01	6000	11.6			
	2.77	6000	1.29				3.05	6000	6.56			
	3.73	6000	1.65				5.49	6000	11.5			
	4.78	6000	1.98				7.62	6000	15.5			
	7.47	6000	2.6				11.13	6000	21.7			
26.67	2.11	6000	1.3			114.3	3.05	6000	8.51			
	2.87	6000	1.71				6.02	6000	16.3			
	3.91	6000	2.23				8.56	6000	22.7			
	5.56	6000	2.94			141.3	3.4	6000	11.8			
	7.82	6000	3.7				6.55	6000	22.1			
33.4	1.65	6000	1.31			168.3	9.53	5500	31.5			
	2.77	6000	2.13				3.4	6000	14.1			
	3.38	6000	2.54				7.1	6000	28.7			
	4.55	6000	3.29				10.97	6000	43.3			
	6.35	6000	4.31				219.1	3.76	6000	20.3		
	9.09	6000	5.54					8.18	6000	43.3		
42.16	2.77	6000	2.74			273.1	12.7	6000	65.7			
	3.56	6000	3.45				9.27	6000	61.3			
	4.85	6000	4.54				12.7	6000	82.9			
	6.35	6000	5.7				15.1	6000	97.7			
48.26	2.77	6000	3.16			323.9	28.6	6000	175			
	3.68	6000	4.11				9.52	6000	75			
	5.08	6000	5.5				10.3	6000	81			
	7.14	6000	7.36				12.7	6000	99.1			
	10.16	6000	9.7									
60.33	2.77	6000	4									
	3.91	6000	5.53									
	5.54	6000	7.61									
	8.74	6000	11.3									
73.03	2.11	6000	3.75									